

コンクリート用振動ドリル EA811AA-2.5～14.5

- ◆コンクリート、ブロック、モルタル、窯業系サイディングの穴あけに
- ◆コンクリート釘の下穴に(φ2.5、φ2.8)



- 3枚刃により作業性、経済性が大幅向上！
- 真円に近い穴あけが可能
- 抜群の耐久性
- 優れた穿孔スピード

振動ドリル

振動ドリル(振動モード)でご使用ください。
インパクトドリル、ドリルドライバーには使用できません。

品番	刃先外径 (mm)	全長 (mm)	有効長 (mm)
EA811AA-2.5	2.5	100	45
EA811AA-2.8	2.8		
EA811AA-3	3.0		
EA811AA-3.2	3.2		
EA811AA-3.3	3.3		
EA811AA-3.4	3.4		
EA811AA-3.5	3.5		50
EA811AA-3.6	3.6		
EA811AA-3.7	3.7		
EA811AA-3.8	3.8		
EA811AA-4	4.0		
EA811AA-4.2	4.2		
EA811AA-4.3	4.3		
EA811AA-4.4	4.4		
EA811AA-4.5	4.5		
EA811AA-4.8	4.8	115	65
EA811AA-5	5.0		
EA811AA-5.2	5.2		
EA811AA-5.3	5.3		
EA811AA-5.4	5.4		
EA811AA-5.5	5.5		
EA811AA-5.8	5.8	125	75
EA811AA-6	6.0		
EA811AA-6.4	6.4		
EA811AA-6.5	6.5		
EA811AA-7	7.0		
EA811AA-7.2	7.2		
EA811AA-7.5	7.5	150	90
EA811AA-8	8.0		
EA811AA-8.5	8.5		
EA811AA-8.7	8.7		
EA811AA-9	9.0		
EA811AA-9.5	9.5	170	120
EA811AA-10	10.0		
EA811AA-10.5	10.5		
EA811AA-11	11.0		
EA811AA-11.5	11.5		
EA811AA-12	12.0		
EA811AA-12.5	12.5		
EA811AA-12.7	12.7		
EA811AA-13	13.0	170	120
EA811AA-13.5	13.5		
EA811AA-14	14.0		
EA811AA-14.3	14.3		
EA811AA-14.5	14.5		