

EA952S-41～EA952S-402 [押しスプリング (1m)]

仕 様：

品 番	外径 (mm)	線径 (mm)	ピッチ (mm)	許容荷重 (kgf)
EA952S-41	4	0.5	2.0	0.5
EA952S-51	5	0.5	2.0	0.4
EA952S-52	5	0.8	2.3	0.4
EA952S-61	6	0.5	2.0	0.3
EA952S-62	6	1.0	2.5	2.6
EA952S-71	7	0.5	2.5	0.3
EA952S-72	7	1.4	3.4	6.0
EA952S-81	8	1.0	3.0	2.0
EA952S-101	10	1.0	4.0	1.6
EA952S-102	10	1.6	4.6	6.6
EA952S-103	10	2.0	4.5	12.7
EA952S-104	10	2.6	5.1	26.5
EA952S-111	11	1.6	4.6	5.9
EA952S-121	12	1.0	4.5	1.4
EA952S-122	12	1.6	4.6	5.4
EA952S-123	12	2.0	4.5	10.4
EA952S-124	12	2.6	5.1	19.7
EA952S-141	14	1.0	5.0	1.1
EA952S-142	14	1.6	4.6	4.7
EA952S-143	14	2.0	5.0	9.0
EA952S-144	14	2.6	5.6	19.9
EA952S-151	15	1.6	5.6	4.1

品 番	外径 (mm)	線径 (mm)	ピッチ (mm)	許容荷重 (kgf)
EA952S-161	16	1.0	5.0	1.0
EA952S-162	16	1.6	6.6	4.1
EA952S-163	16	2.0	7.0	8.2
EA952S-164	16	2.6	6.6	16.6
EA952S-165	16	3.0	6.0	26.4
EA952S-171	17	1.6	5.6	3.9
EA952S-181	18	2.0	7.0	7.3
EA952S-182	18	2.6	7.6	15.7
EA952S-183	18	3.0	6.5	21.9
EA952S-191	19	2.0	6.0	6.5
EA952S-201	20	2.0	6.0	6.6
EA952S-202	20	2.6	6.6	13.8
EA952S-203	20	3.0	7.0	21.3
EA952S-204	20	3.5	6.5	33.7
EA952S-205	20	4.0	8.0	50.0
EA952S-221	22	2.0	6.5	5.9
EA952S-222	22	2.6	6.6	12.6
EA952S-223	22	3.0	7.0	19.0
EA952S-224	22	3.5	8.5	30.5
EA952S-225	22	4.0	8.0	44.7
EA952S-231	23	3.5	7.5	29.3
EA952S-241	24	2.0	7.0	5.4

品 番	外径 (mm)	線径 (mm)	ピッチ (mm)	許容荷重 (kgf)
EA952S-242	24	2.6	7.6	11.7
EA952S-243	24	3.0	7.0	27.7
EA952S-244	24	3.5	7.5	41.3
EA952S-245	24	4.0	8.0	41.5
EA952S-261	26	2.0	6.5	5.0
EA952S-262	26	3.0	7.0	16.4
EA952S-263	26	3.5	8.5	26.3
EA952S-264	26	4.0	9.0	37.9
EA952S-281	28	3.5	8.5	24.4
EA952S-282	28	4.0	10.0	36.1
EA952S-301	30	3.5	9.5	22.9
EA952S-302	30	4.0	9.0	33.8
EA952S-303	30	5.0	10.0	64.9
EA952S-321	32	4.0	9.0	31.8
EA952S-341	34	4.0	9.0	30.0
EA952S-351	35	3.5	9.5	19.6
EA952S-361	36	4.0	9.0	28.2
EA952S-362	36	5.0	10.0	55.0
EA952S-381	38	4.0	9.0	26.7
EA952S-382	38	5.0	10.0	51.7
EA952S-401	40	4.0	9.0	25.2
EA952S-402	40	5.0	11.0	49.5

●材質…バネ鋼

●長さ…1m

※許容荷重は1mの長さで使用された場合の数値です。