



EA164FB-30 ~ -90 (1")インパクトソケット

- 6ポイント
- 差込角 1"



	サイズ(mm)	D1(mm)	D2(mm)	l(mm)	L(mm)	適用ピン	適用Oリング	重量(g)
EA164FB-30	30	49	54	21	62	EA164AA -6A	EA164A -45B	657
EA164FB-31	31	50.3	54	21	62			687
EA164FB-32	32	51.5	54	21	62			685
EA164FB-33	33	52.8	54	21	62			685
EA164FB-34	34	54	54	21	62			690
EA164FB-35	35	55.3	54	21	62			710
EA164FB-36	36	56.5	54	21	62			712
EA164FB-37	37	57.8	54	21	62			735
EA164FB-38	38	59	54	25	66			720
EA164FB-40	40	61.5	54	25	66			850
EA164FB-41	41	62.8	54	25	66			850
EA164FB-42	42	64	54	25	66			905
EA164FB-43	43	65.3	54	27	68			977
EA164FB-45	45	67.8	54	27	68			963
EA164FB-46	46	69	54	29	70			1010
EA164FB-47	47	70.3	54	36	70			997
EA164FB-48	48	71.5	54	35	70			990
EA164FB-50	50	74	54	35	70			1065
EA164FB-52	52	76.5	54	40	75			1185
EA164FB-54	54	79	54	40	75			1252
EA164FB-55	55	80.3	54	39	75			1260
EA164FB-56	56	81.5	54	39	75			1277
EA164FB-58	58	84	54	39	75			1340
EA164FB-60	60	86.5	54	39	75			1400
EA164FB-62	62	89	54	38	75			1410
EA164FB-63	63	90.3	54	38	75			1383
EA164FB-65	65	92.8	54	38	75			1630
EA164FB-68	68	96.5	54	37	75			1583
EA164FB-70	70	99	54	37	75			1625
EA164FB-75	75	105.3	86	39	80	EA164AA- 6B	EA164A -75	2675
EA164FB-80	80	111.5	86	44	85			2996
EA164FB-85	85	117.8	86	46	90			3378
EA164FB-90	90	124	86	51	95			3871


(例)



インパクトソケット用Oリング (別売)



インパクトソケット用ピン (別売)



インパクトソケット (別売)

必ずインパクトソケット用ピン、Oリングを併用してください。